


Installing Two Node RAC in Amazon Cloud



Node Configurations

Details	Sto.geeklabs.com	Db1.geeklabs.com	Db2.geeklabs.com
AWS Type	Ec2	Ec2	Ec2
Instance Class	M3.medium	M3.medium	M3.medium
Multicast Support	Ntop- Super Node	Ntop – edge	Ntop-edge
Shared Storage	iSCSi Target	iSCSi Initiator	iSCSi Initiator
Storage Type	EBS/Magnetic	EBS/Magnetic	EBS/Magnetic
Storage Size	Root Volume – 20gb EBS Volumes – 10 gb * 2	Root Volume- 20gb	Root Volume -20gb
VPC	Custom VPC Internet gate Way Enabled	Custom VPC Internet gate Way Enabled	Custom VPC Internet gate Way Enabled
Public Subnet	Subnet 1 : 10.0.0.74	Subnet 1 : 10.0.0.233	Subnet 1 : 10.0.0.83
Secondary Public IP's	Nil	Subnet 1 : 10.0.0.100 (VIP) Subnet 1 : 10.0.0.101 (SCAN) Subnet 1 : 10.0.0.102 (SCAN) Subnet 1 : 10.0.0.103 (SCAN)	Subnet 1 : 10.0.0.104 (VIP)
Private Subnet	Nil	Subnet 2: 10.0.1.21	Subnet 2: 10.0.1.22
OS - AWS Image	OEL 5.11 UEK ami-c5b2dfff	OEL 5.11 UEK ami-c5b2dfff	OEL 5.11 UEK ami-c5b2dfff

High Level Steps

1. Configuring Custom VPC & Public & Private Subnets
2. Create AWS Linux EC2 Instance with AWS Cli Tools
3. Creating a Key Pair & Download
4. Creating & Configuring Storage Node
5. Creating & Configuring Database Nodes (db1,db2)
6. Install & Configure 12c Grid Infrastructure
7. Install & Configure 12c RAC Database

Configuring Custom VPC & Public & Private Subnets

#Creating & Configuring VPC

```
aws ec2 create-vpc --cidr-block 10.0.0.0/16
aws ec2 create-tags --tags Key=Name,Value=MyRacVPC --resources vpc-c90f2828
aws ec2 modify-vpc-attribute --vpc-id vpc-c90f2828 --enable-dns-support
aws ec2 modify-vpc-attribute --vpc-id vpc-c90f2828 --enable-dns-hostnames
```

#Creating & Configuring Internet Gateway

```
aws ec2 create-internet-gateway
aws ec2 attach-internet-gateway --internet-gateway-id igw-928503f7 --vpc-id vpc-c90f2828
aws ec2 describe-route-tables --filters "Name=vpc-id,Values=vpc-c90f2828"
aws ec2 create-route --route-table-id rtb-66c52922 --destination-cidr-block 0.0.0.0/0 --gateway-id igw-928503f7
aws ec2 create-subnet --vpc-id vpc-c90f2828 --cidr-block 10.0.0.0/24
aws ec2 create-tags --resources subnet-ff223939 --tags Key=Name,Value=Subnet1
```

#Creating & Configuring Security Group

```
aws ec2 create-security-group --group-name MyRACSecurityGroup --description "My RAC Security Group" --vpc-id vpc-c90f2828
aws ec2 authorize-security-group-ingress --group-id sg-2ae22282 --protocol -1 --port -1 --source-group sg-2ae22282
```

#Creating Security Key Pair

```
aws ec2 create-key-pair --key-name MyRACKeyPair
chmod 600 MyRACKeyPair.pem
```

#Creating Storage Node

```
aws ec2 run-instances --image-id ami-c5b2dfff --instance-type m3.medium --key MyRACKeyPair \
--placement AvailabilityZone=ap-southeast-2b --associate-public-ip-address --subnet subnet-ff223939 \
--private-ip-address 10.0.0.11 --security-group-ids sg-2ae22282 \
--block-device-mappings
' [{"DeviceName": "/dev/xvda", "Ebs": {"VolumeSize": 15, "DeleteOnTermination": true, "VolumeType": "standard"}} ] \
--block-device-mappings
' [{"DeviceName": "/dev/xvdb", "Ebs": {"VolumeSize": 10, "DeleteOnTermination": true, "VolumeType": "standard"}} ] \
--block-device-mappings
' [{"DeviceName": "/dev/xvdc", "Ebs": {"VolumeSize": 10, "DeleteOnTermination": true, "VolumeType": "standard"}} ] \

aws ec2 create-tags --resources i-79aewi22 --tags Key=Name,Value=sto1
```

#Creating DB1 Node

```
aws ec2 run-instances --image-id ami-c5b2dfff --instance-type m3.medium --key MyRACKeyPair \
--placement AvailabilityZone=ap-southeast-2b --associate-public-ip-address --subnet subnet-ff223939 \
--private-ip-address 10.0.0.11 --secondary-private-ip-address-count 4 --security-group-ids sg-2ae22282 \
--block-device-mappings
' [{"DeviceName": "/dev/xvda", "Ebs": {"VolumeSize": 20, "DeleteOnTermination": true, "VolumeType": "standard"}} ]'

aws ec2 create-tags --resources i-7e7375bb --tags Key=Name,Value=db1
```

#Creating DB2 Node

```
aws ec2 run-instances --image-id ami-c5b2dfff --instance-type m3.medium --key MyRACKeyPair \
--placement AvailabilityZone=ap-southeast-2b --associate-public-ip-address --subnet subnet-ff223939 \
--private-ip-address 10.0.0.11 --secondary-private-ip-address-count 1 --security-group-ids sg-2ae22282 \
--block-device-mappings
' [{"DeviceName": "/dev/xvda", "Ebs": {"VolumeSize": 20, "DeleteOnTermination": true, "VolumeType": "standard"}} ]'

aws ec2 create-tags --resources i-7e7375bb --tags Key=Name,Value=db2
```

Configure Storage Node

1. Install Oracle Validated Package

```
yum install oracle-validated -y
yum install unzip -y
yum install unzip -y
yum update perl -y
yum install perl -y
yum install net-snmp -y
yum install net-snmp-utils -y
yum install "perl(LWP)" -y
yum -y install svn make gcc s3cmd -y
yum -y install svn -y
yum -y install subversion make gcc s2cmd -y
yum install scsi-target-utils -y
```

2. Configure Network & HostName

```
cp /etc/sysconfig/network /etc/sysconfig/network.orig
sed 's/^HOSTNAME=.* /HOSTNAME=sto1.geekslabs.com/' /etc/sysconfig/network.orig
>/etc/sysconfig/network
echo "`ifconfig eth0 | grep "inet addr" | cut -d ":" -f2 | cut -d " " -f1` sto1.geekslabs.com sto1"
>> /etc/hosts
```

3. Configure Swap Disk

```
dd if=/dev/zero of=/swapfile1 bs=1024 count=2097152
chown root:root /swapfile1
chmod 0600 /swapfile1
mkswap /swapfile1
swapon /swapfile1
vi /etc/fstab
    /swapfile1 none swap sw 0 0
```

4. Install Ntop – SuperNode & Edge

```
svn co https://svn.ntop.org/svn/ntop/trunk/n2n
cd n2n_v2
sed -i "s/#N2N_OPTION_AES=no/N2N_OPTION_AES=no/g" Makefile
sed -i "s/#define N2N_COMPRESSION_ENABLED 1/#define N2N_COMPRESSION_ENABLED 0/g" n2n.h
make
cp ./supernode /usr/bin/
supernode -l 1200
```

5. Install iSCSi Target & Configure Disks

```
fdisk /dev/xvdb
input → n
input → p
input → 1
input → enter
input → enter
input → w
Repeat for disk /dev/xvdc
```

```
service tgtd start
chkconfig tgtd on
vi /etc/tgt/targets.conf
    <target sto1:drive1>
        backing-store /dev/xvdb1
        backing-store /dev/xvdc1
    </target>
service tgtd restart
```

6. Disable Firewall

```
service iptables stop
chkconfig iptables off
```

Configure db1 node

1. Install Oracle Validated Package

```
yum install oracle-validated -y
yum install oracle-rdbms-server-12cR1-preinstall -y
yum install unzip -y
yum install unzip -y
yum update perl -y
yum install perl -y
yum install net-snmp -y
yum install net-snmp-utils -y
yum install "perl(LWP)" -y
yum -y install svn make gcc s3cmd -y
yum -y install svn -y
yum -y install subversion make gcc s2cmd -y
yum install scsi-target-utils -y
yum install iscsi-initiator-utils -y
```

2. Install Ntop Edge and configure Private Network

Copy the edge binary from sto1 server to db1 host

```
scp edge db1.geekslabs.com:/usr/bin/edge
```

#Start the edge service and enable route

```
edge -l stocell1:1200 -c Intershop -a 10.1.0.21 -E >> /etc/rc.local
route add -net 224.0.0.0 netmask 240.0.0.0 dev edge0
route add -net 169.254.0.0 netmask 255.255.0.0 dev edge0
```

3. Configure Public Network

#Get the IP Addresses & Update the /etc/hosts

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '5p' db1.geekslabs.com db1" >> /etc/hosts
```

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '1p' db1-vip.geekslabs.com db1-vip"
```

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '2p' db-scan.geekslabs.com db-scan"
```

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '3p' db-scan.geekslabs.com db-scan"
```

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '4p' db-scan.geekslabs.com db-scan"
```

4. Configure Storage Server Details

#Get the IP Addresses & Update the /etc/hosts

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail -n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '5p'` sto1.geekslabs.com sto1" >> /etc/hosts
```

5. Configure iSCSI Initiator and Scan the disks from Storage Server

```
service iscsi start
chkconfig iscsi on
scsiadm --mode discoverydb --type sendtargets --portal sto1:3260 --discover
service iscsi restart
```

6. Configure Oracleasm and provision the disks

#Download the oracleasm rpm

```
wget http://oss.oracle.com/projects/oracleasm-support/dist/files/RPMS/rhel5/amd64/2.1.8/oracleasm-support-2.1.8-1.el5.x86\_64.rpm
```

```
wget http://download.oracle.com/otn\_software/asmlib/oracleasmlib-2.0.4-1.el5.x86\_64.rpm
```

#Install the RPMS's

```
rpm -ivu oracleasm-support-2.1.8-1.el5.x86_64.rpm oracleasmlib-2.0.4-1.el5.x86_64.rpm
```

#Install the oracleasm

```
oracleasm configure -i
input → oracle
input → oinstall
input → y
input → y
```

#Create Provision Disk

```
oracleasm createdisk CRSVOL1 /dev/xvdb1
oracleasm createdisk DATAVOL1 /dev/xvdc1
```

#Scan & List Disks

```
oracleasm scandisks
oracleasm listdisks
```

7. Disable NTP & Firewall

```
service ntpd stop; chkconfig ntpd off
mv /etc/ntp.conf /etc/ntp.conf.orig ; rm /var/run/ntpd.pid ; service iptables stop ; chkconfig iptables off
```

Configure db2 node

1. Install Oracle Validated Package

```
yum install oracle-validated -y
yum install oracle-rdbms-server-12cR1-preinstall -y
yum install unzip -y
yum install unzip -y
yum update perl -y
yum install perl -y
yum install net-snmp -y
yum install net-snmp-utils -y
yum install "perl(LWP)" -y
yum -y install svn make gcc s3cmd -y
yum -y install svn -y
yum -y install subversion make gcc s2cmd -y
yum install scsi-target-utils -y
yum install iscsi-initiator-utils -y
```

2. Install Ntop Edge and configure Private Network

Copy the edge binary from sto1 server to db1 host

```
scp edge db2.geekslabs.com:/usr/bin/edge
```

#Start the edge service and enable route

```
edge -l stocell1:1200 -c Intershop -a 10.1.0.22 -E >> /etc/rc.local
route add -net 224.0.0.0 netmask 240.0.0.0 dev edge0
route add -net 169.254.0.0 netmask 255.255.0.0 dev edge0
```

3. Configure Public Network

#Get the IP Addresses & Update the /etc/hosts

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '5p' db2.geekslabs.com db2" >> /etc/hosts
```

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '1p' db2-vip.geekslabs.com db2-vip"
```

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '2p' db-scan.geekslabs.com db-scan"
```

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '3p' db-scan.geekslabs.com db-scan"
```

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail
-n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '4p' db-scan.geekslabs.com db-scan"
```

4. Configure Storage Server Details

#Get the IP Addresses & Update the /etc/hosts

```
echo "`aws ec2 describe-instances --instance-id "i-398879e8" | grep "PrivateIpAddress" | tail -n +4 | head -5 | cut -d ':' -f2 | tr -d ' "' | sed -n '5p'" sto1.geekslabs.com sto1" >> /etc/hosts
```

5. Configure iSCSI Initiator and Scan the disks from Storage Server

```
service iscsi start
chkconfig iscsi on
scsiadm --mode discoverydb --type sendtargets --portal sto1:3260 --discover
service iscsi restart
```

6. Configure Oracleasm and provision the disks

#Download the oracleasm rpm

```
wget http://oss.oracle.com/projects/oracleasm-support/dist/files/RPMS/rhel5/amd64/2.1.8/oracleasm-support-2.1.8-1.el5.x86\_64.rpm
```

```
wget http://download.oracle.com/otn\_software/asmlib/oracleasmlib-2.0.4-1.el5.x86\_64.rpm
```

#Install the RPMS's

```
rpm -ivU oracleasm-support-2.1.8-1.el5.x86_64.rpm oracleasmlib-2.0.4-1.el5.x86_64.rpm
```

#Install the oracleasm

```
oracleasm configure -i
```

```
input → oracle
```

```
input → oinstall
```

```
input → y
```

```
input → y
```

#Scan & List Disks , Disk Should be visible if not check you are reachable to sto1 server

```
oracleasm scandisks
```

```
oracleasm listdisks
```

7. Disable NTP & Firewall

```
service ntpd stop; chkconfig ntpd off
mv /etc/ntp.conf /etc/ntp.conf.orig ; rm /var/run/ntpd.pid ; ; service iptables stop ; chkconfig iptables off
```

Installing Grid Infrastructure

1. Copy the Software

```
Using winscp if you already have a software or download from the oracle site
mkdir /u01/stage
wget
cd /u01/stage
unzip *.zip
```

2. Create Directories & Update Permissions

```
mkdir -p /u01/app/12.1.0.1/grid
mkdir -p /u01/app/oracle/product/12.1.0.1/db_1
chown -R oracle:oinstall /u01
chmod -R 775 /u01/
```

3. Run Userequivalency Setup

```
cd /u01/stage/grid
./sshUserSetup.sh -user oracle -hosts "db1 db2" -noPromptPassphrase
```

4. Run Cluster Verification Utility

```
cd /u01/stage/grid
runcluvfy.sh stage -pre crsinst -n ol6-121-rac1,ol6-121-rac2 -verbose
```

5. Edit the response file , vi /u01/stage/grid/response/grid_response.rsp (change as below)

```
< ORACLE_HOSTNAME=db1.geekslabs.com
< INVENTORY_LOCATION=/u01/app/oraInventory
< oracle.install.option=CRS_CONFIG
< ORACLE_BASE=/u01/app/oracle
< ORACLE_HOME=/u01/app/12.1.0.1/grid
< oracle.install.asm.OSDBA=asmdba
< oracle.install.asm.OSASM=asmadmin
< oracle.install.crs.config.gnp.scanName=myrac-scan.geekslabs.com
< oracle.install.crs.config.gnp.scanPort=1521
< oracle.install.crs.config.ClusterType=STANDARD
< oracle.install.crs.config.clusterName=geekcluster
< oracle.install.crs.config.gnp.configureGNS=false
< oracle.install.crs.config.autoConfigureClusterNodeVIP=false
< oracle.install.crs.config.clusterNodes=db1.geekslabs.com:myrac01-
vip.geekslabs.com,db2.geekslabs.com:myrac02-vip.geekslabs.com
< oracle.install.crs.config.networkInterfaceList=eth0:10.0.0.1,edge0:10.1.0.0:2
< oracle.install.crs.managementdb.configure=false
< oracle.install.crs.config.storageOption=LOCAL_ASM_STORAGE
< oracle.install.crs.config.useIPMI=false
< oracle.install.asm.SYSASMPassword=admin123
< oracle.install.asm.diskGroup.name=OCRDG
< oracle.install.asm.diskGroup.redundancy=EXTERNAL
<
oracle.install.asm.diskGroup.disks=/dev/oracleasm/disks/CRSVOL1,/dev/oracleasm/disks/CRSVOL2,/dev/oracleasm/d
isks/CRSVOL3
< oracle.install.asm.diskGroup.diskDiscoveryString=/dev/oracleasm/disks/*
< oracle.install.asm.monitorPassword=admin123
```

6. Run Installer

```
cd /u01/stage/grid
./runInstaller -silent -responseFile /home/oracle/grid_install.rsp -
ignoreSysprereqs -showProgress -ignorePrereq
```

7. Run Root.sh in Node 1

```
cd /u01/app/oraInventory
./orarootInst.sh

Cd /u01/app/12.1.0.1/grid
./root.sh

*** IMPORTANT DO NOT SKIP* Root.sh may fail in node 2, due to HAIP issues, to fix this log to ASM Instance in db1 and set cluster_interconnect parameters

su - oracle
. oraenv
+ASM1
sqlplus / as sysasm
SQL> alter system set cluster_interconnects="10.0.1.21" scope=spfile sid='+ASM1';
SQL> alter system set cluster_interconnects="10.0.1.22" scope=spfile sid='+ASM2';
```

8. Run Root.sh in Node 2

```
cd /u01/app/oraInventory
./orarootInst.sh

Cd /u01/app/12.1.0.1/grid
./root.sh
```

9. Configure Failover for SCAN & VIP (EC2 Specific)

```
#Run the Configure_EC2_VIP.sh to configure a Elastic VIP Failover (Specific to AWS as EC2 ip cannot failover)

Place the scripts ec2_vip_failover.sh to /etc/oracle
Copy the Configure_EC2_VIP.sh to /home/oracle
cd/home/oracle
./Configure_EC2_VIP.sh
```

10. Check the status of the Cluster

```
crsctl stat res -t -init
crsctl stat res -t
```

Installing RAC Database

1. Copy the Software
2. Edit the Response File, vi /u01/stage/database/response/db_install.rsp

```
oracle.install.option=INSTALL_DB_SWONLY
ORACLE_HOSTNAME=db1
UNIX_GROUP_NAME=oinstall
INVENTORY_LOCATION=/u02/app/oraInventory
ORACLE_HOME=/u01/app/oracle/product/12.1.0/db_1
ORACLE_BASE=/u01/app/oracle
oracle.install.db.InstallEdition=EE
oracle.install.db.DBA_GROUP=dba
oracle.install.db.OPER_GROUP=oper
oracle.install.db.BACKUPDBA_GROUP=dba
oracle.install.db.DGDBA_GROUP=asmadmin
oracle.install.db.KMDBA_GROUP=dba
SECURITY_UPDATES_VIA_MYORACLESUPPORT=false
DECLINE_SECURITY_UPDATES=true
```

3. Install Database Software

```
Cd /u01/stage/database
./runInstaller -silent -ignoreprereqs -responsefile
/home/oracle/database/response/db_install.rsp
```

Once installed, run root.sh in both nodes

4. Create Disk Group DATA to hold the database files

```
On db1 node as Oracle User
. oraenv
+ASM1
sqlplus / as sysasm
create diskgroup DATA external redundancy disk '/dev/oracleasm/disks/DATAVOL1';
alter diskgroup DATA set attribute 'compatible.rdbms'='12.1.0' ;
srvctl start diskgroup DATA -n db2
```

5. Create Database Using DBCA

```
./dbca -silent \  
-createDatabase \  
-templateName General_Purpose.dbc \  
-gdbName db12c \  
-sid db12c \  
-SysPassword oracle123 \  
-createAsContainerDatabase true \  
-numberOfPDBs 1 \  
-pdbName PDB1 \  
-SystemPassword oracle123 \  
-emConfiguration NONE \  
-redoLogFileSize 100 \  
-recoveryAreaDestination FRA \  
-storageType ASM \  
-asmnmpPassword oracle123 \  
-asmSysPassword oracle123 \  
-diskGroupName DATA \  
-listeners LISTENER \  
-registerWithDirService false \  
-characterSet AL32UTF8 \  
-nationalCharacterSet AL16UTF16 \  
-databaseType MULTIPURPOSE \  
-nodelist db1,db2 \  
-initparams  
audit_file_dest='/u01/app/oracle/admin/db12c/adump' \  
-initparams compatible='12.1.0.0' \  
-initparams db_create_file_dest='+DATA' \  
-initparams db_create_online_log_dest_1='+DATA' \  
-initparams db_create_online_log_dest_2='+DATA\  
-initparams db_recovery_file_dest='+DATAA' \  
-initparams pga_aggregate_target=100M \  
-initparams diagnostic_dest='/u01/app/oracle' \  
-initparams parallel_max_servers=8 \  
-initparams processes=400 \  
-initparams sga_target=524288000 \  
-initparams db_recovery_file_dest_size=4322230272
```